



Customer Care

+91 90999 30536

Marketed By :

ITALIAN CERA LLP

Near Mahendra nagar Chokdi, Halvad Road, Morbi - 363641

E-mail : info.italiancerachem@gmail.com | Web : WWW.ITALIANCERA.COM

Disclaimer: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out taste & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the result obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the usage of our products.

IS : 15477

CM/L - 7900135518



WATERPROOF SUPERIOR GRIP EASY TO APPLY



**#BONDING
KA
BADSHAH**



ABOUT US

ITALIANCERA LLP is your one stop solution for everything related to Construction Chemicals, Epoxy, Adhesives, Admixtures, Sealers and other various application like grouting, fixing tilex, waterproofing. At Italiancera we have implemented world class practices that ensure our products lasts long. Bid good bye to all your worries with regards to chemicals. Say hello to a worry free future, say hello to ITALIANCERA LLP

TILES ADHESIVE

- NSA 2 STAR 01 - 02
- NSA 3 STAR 03 - 04
- NSA 4 STAR 05 - 06
- NSA 5 STAR 07 - 08
- BLOCK JOINTING 09 - 10
- WALL PUTTY 11 - 12
- TILE GROUT 13 - 14
- GROUT ADMIX 15 - 16
- EPOXY-3 PART 17 - 18





2 STAR TILE ADHESIVE

Packing 20 kg
Available in Grey Color

01

NSA 2 STAR Tiling Solution



02

Product Details

ITALIAN CERA NSA 2 STAR (Grey) is a high polymer modified, cement-based tile adhesive which is suitable for fixing tiles, cement torazzo, concrete floor, natural stones, vitrified tiles in interior and exterior floor areas.

Application Area

Applying Ceramic Wall Tiles & Floor Tiles (12x12, 12x18, 400x400, 600x600)

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hassles of mixing the ingredients.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing
Store in a cool & dry place.

NSA 2 STAR	
Bulk Density	1400-1500 Kg/m ³
Water Powder Ratio	25%
Pot Life	30 Min,
Open Time	30 Min,
Adjustable Time	30 Min,
Usage Time Post Application	24 hrs
Compressive Strength @ 28 Days	7-8 N/mm
Slip Resistance @ 20 kg/sq.m.	0 mm
Coverage @3mm Per Kg	4 Sq. Ft.
Tensile Strength	>1450 N Force
Shear Adhesive Strength. M Pa	8-10

02



3 STAR TILE ADHESIVE

Packing 20 kg
Available in Grey Color

NSA 3 STAR Tiling Solution



Product Details

ITALIAN CERA NSA 3 STAR (Grey) is a high polymer modified, adhesive for vitrified, granite on wall cladding and floor for internal & external use.

Application Area

Applying Interior and exterior-Tile on Tile Wall & Vitrified floor Tiles (12x24, 600x1200,) up to 10 Feet.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing
Store in a cool & dry place.

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hassles of mixing the ingredients.

NSA 3 STAR	
Bulk Density	1400-1500 Kg/m ³
Water Powder Ratio	25%
Pot Life	30 Min,
Open Time	30 Min,
Adjustable Time	30 Min,
Usage Time Post Application	24 hrs
Compressive Strength @ 28 Days	7-8 N/mm
Slip Resistance @ 20 kg/sq.m.	0 mm
Coverage @3mm Per Kg	4 Sq. Ft.
Tensile Strength	>1450 N Force
Shear Adhesive Strength. M Pa	8-10



4 STAR TILE ADHESIVE

Packing 20 kg

Available in Grey Color

NSA 4 STAR Tiling Solution



Product Details

ITALIAN CERA NSA 4 STAR (Grey) is a high polymer modified, Gray/white cement based, high performance, high strength and high quality tile adhesive developed to fix glass mosaic, italian marble and special tiles suitable for both internal and external, thin bed applications.

Application Area

Applying vitrified wall and tiles an wall externally (600x600mm, 600x1200mm, 12x12mm. 800x800mm, 800x1600mm, 800x2400 mm) up to 30 feet.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing
Store in a cool & dry place.

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hassles of mixing the ingredients.
- ▶ Applying small size marble & granites on wall exterlty (up to 800x1200mm)

NSA 4 STAR

Bulk Density	1400-1500 Kg/m ³
Water Powder Ratio	25%
Pot Life	30 Min,
Open Time	30 Min,
Adjustable Time	30 Min,
Usage Time Post Application	24 hrs
Compressive Strength @ 28 Days	7-8 N/mm
Slip Resistance @ 20 kg/sq.m.	0 mm
Coverage @3mm Per Kg	4 Sq. Ft.
Tensile Strength	>1450 N Force
Shear Adhesive Strength. M Pa	8-10



5 STAR TILE ADHESIVE

Packing 20 kg

Available in Grey Color

NSA 5 STAR Tiling Solution



Product Details

ITALIAN CERA NSA 5 STAR (Grey) is a high polymer modified cementitious wall and floor tile adhesive specially formulated for fixing mosaic tiles ceramic, glass mosaic etc. it is also suitable for fixing ceramic, vitrified wall & floor metal or glass tiles, marble, granitro quartz stone, terrazzo and other natural stone in interior and exterior locations which includes use in swimming pools.

Application Area

Applying vitrified wall and tiles an wall externally (600x600mm, 600x1200mm, 800x800mm, 800x1600mm, 1600x3200 mm, Granito) up to 30 feet.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing
Store in a cool & dry place.

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hossles of mixing the ingredients.

NSA 5 STAR

Bulk Density	1400-1500 Kg/m ³
Water Powder Ratio	25%
Pot Life	30 Min,
Open Time	30 Min,
Adjustable Time	30 Min,
Usage Time Post Application	24 hrs
Compressive Strength @ 28 Days	7-8 N/mm
Slip Resistance @ 20 kg/sq.m.	0 mm
Coverage @3mm Per Kg	4 Sq. Ft.
Tensile Strength	>1450 N Force
Shear Adhesive Strength. M Pa	8-10



BLOCK JOINTING MATERIAL FOR JOINTING AAC BLOCKS

Packing 40 kg
Available in Grey Color

IC-BLOCK JOINTING Tiling Solution



Product Details

High polymer modified adhesive, High Performance flexible adhesive suitable for glass mosaic, High tensile strength, Flexible tile adhesive, water resistance, easy to use, Glass & mosaic adhesive exceeds the requirements of Specification for adhesives for use with Mosaics

Application Area

Use For Fly ASH LB-Block Adhesion

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastage
- No curing required
- Single component no hassles of mixing the ingredients.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing
Store in a cool & dry place.



WALL PUTTY POLYMER MODIFIED FINE PREMIUM QUALITY PUTTY

Packing 40 kg

Available in White Color

WALL PUTTY Tiling Solution



Product Details

ITALIAN CERA Wall Putty (White) is a highly polymer modified cementitious wall and floor tile adhesive specially formulated for fixing mosaic tiles ceramic, glass mosaic etc. it is also suitable for fixing ceramic, vitrified wall & floor metal or glass tile, marble, granite quartz stone, terrazzo and other natural stone and exterior locations which includes use in swimming pools

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hassles of mixing the ingredients.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing
Store in a cool & dry place.



TILE GROUT

ONE PACK WATER RESISTANT TILE GROUT

Packing 1kg

TILE GROUT



Product Details

ITALIAN CERA Tile Grout is a grey, high polymer modified, cement-based tile adhesive which is suitable for fixing tiles, natural stone, vitrified tiles in interior and exterior situations. Consult ITALIAN CERA Chemicals regarding use of a higher performance adhesive for applications in difficult and demanding situations.

Shelf life & storage

Shelf life is 24 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

Application Area

Wall, Floor, Interior & Exterior Dry Area Work Tops.

Colors





GROUT ADMIX

FOR BATTER STRENGTH OF GROUT

Packing 200 ml

GROUT ADMIX

Product Details

ITALIAN CERA Admix is specially designed latex admix to be used with Sanded & Unsanded Grout

Shelf life & storage

It improves the performance of Portland cement grouts for all type of ceramic tile, brick, marble, natural stone and agglomerate stone installations

Application Area

- Colour-fastness
- Flexibility
- Compressive strength
- Shock and chemical resistant
- Reduces water absorption
- Easy to clean

Coverage

Varies as per application





EPOXY-3 PART

STAIN FREE GROUT FOR
FLOOR & WALL (3 PART)

Packing 1kg, 5kg

EPOXY-3 PART



Product Details

ITALIAN CERA Epoxy is a hygienic, hard-wearing, impervious, epoxied resin-based grout with a high degree of resistance to chemical attack, abrasion and impact. The cured grout does not transfer taints to foodstuffs and does not permit the entry of bacteria or dirt. It is easily maintained in a sterile condition.

Technical Specification

Joint Width	Pot Life @27±2°C	Cure @27±2°C	Temperature Resistance	Water Absorption	Specific Gravity
2-20mm	45 minutes	48 hours	Prolonged - 30°C to 150°C Intermittent	Nil(1)	1.75
Tensile Adhesion (14 days air)					
			Dry condition	Wet condition	
Epoxy Grout					
BS 5980:1980					
					(2)

Packaging of Rainbow Sparkle Series

Kit	Filler	Resin	Hardener
5kg	3600gm	1000ml	400ml
1kg	700gm	200ml	100ml

Packaging of ITALIAN CERA Series

Kit	Filler	Resin	Hardener
5kg	3600gm	1000ml	400ml
1kg	700gm	200ml	100ml

#BONDING KA BAOSHAH

